



Non-incendive mobile phone **x.com H201 -Ex**

ecom instruments' reliable mobile phone for Class 1, Division 2 classified hazardous locations.

Withstanding extreme conditions the explosion protected GSM phone **x.com H201 -Ex** with rugged construction and outstanding durability provides all you need to talk safely.



Also available in black.

The mobile phone is based on the extremely rugged and well known Sonim XP3.2 Quest Pro — drop it from 6.5 feet onto concrete; use it for weeks without charging; submerge it in water; leave it outside at -4 to +122 degrees Fahrenheit; cover it in dust; and never get lost with A-GPS.

Providing reliable communications within the harsh environments often faced by today's engineer is a walk in the park for the **x.com H201 -Ex**, it's waterproof (IP67) casing can withstand extreme temperatures while the keyboard touch buttons are tested to function beyond 500,000 pushes.

When it comes to menus and applications the **x.com H201 -Ex**'s simple and intuitive menus provide engineers all of the functionality they would expect with no complicated gimmicks often featured on modern mobile phones.

Triband coverage and impressive battery life mean you need never miss a call again, while fully functioning vibration alert and a loud, audible microphone mean ringtones are easier to hear in noisy environments.

With extreme durability, ultra-bright display and exceptional functionality the **x.com H201 -Ex** is an engineer's new best friend.

- Motorised vibration alarm
- IP 67
- GSM 850/1800/1900
- Bluetooth 2.0
- GPRS & EDGE

- WAP 2.0 and Opera browser
- Java™ 2.0 ME
- Extremely scratch and impact-resistant display
- Free software for data transfer and synchronisation
- Integrated Office functionality
- Outlook synchronisation
- Rechargeable 1850 mAh Li-ion battery
- Micro SD Card slot (up to 2 GB)

Standard delivery:

- **x.com H201 -Ex**
- Battery AMX H20x
- Charger
- USB Data cable
- Stereo wired headset (non-Ex)
- Belt holder
- Safety information
- Instruction manual

Ex-data:

Ex-designation:
NI Class 1 Division 2 A-DT4

Technical data:

Networks:	Triband GSM 850 / 1800 / 1900 MHz
Data transfer:	GPRS
Display:	LCD Display with 65,536 colours (resolution 176 x 220 pixel)
Power supply:	1850 mAh Li-ion battery
Talk time / standby:	max. 18 hrs / max. 1500 hrs
Charging time:	approx. 3 hrs
Dimensions:	119 x 56 x 25 mm
Weight:	approx. 170 g
Ambient temperature Ta:	-20 °C ... +50 °C
IP protection class:	IP 67